

POTENTIOMETERS

Normal Slide Type

Application

- ✓ Audio, Home appliance, Lighting control, etc.

Feature

- ✓ Smooth Slide Feeling



■Specification

| | |
|-----------------------------|--------------------------------|
| Travel Distance | 60mm |
| Insulation Resistance | 100 M Ω Min. at 500V DC |
| Dielectric Strength | 500V AC , 1 minute |
| Operating Temperature Range | -10 °C~70°C |
| Operating Force | 50~350 gf.cm |
| Sliding Life | 15,000 cycles |

■How to order

RA6040F-30 – 15C2 - B10K

[Model](#)

[Lever Type](#)

Taper and Resistance Value

Ex:

| Order Code | Taper | Resistance Value |
|------------|----------|------------------|
| A100K | Log/A | 100K Ω |
| B1M | Linear/B | 1M Ω |

Taper: A and B

Resistance Value: 1K Ω to 500K Ω and 1M Ω

*Contact us for other requirements.

Normal Slide Type

Model Description

| Model | Number of unit | Travel Distance | Type of Terminal |
|------------|----------------|-----------------|-----------------------|
| RA6040F-30 | Single Unit | 60mm | PC board (horizontal) |

| Order Code | Outline Drawing |
|------------|-----------------|
| RA6040F-30 | |

Lever Type

| Model | RA6040F | | | | | | | | | | | |
|------------|------------------|----|----|----|----|----|----|----|----|----|----|--|
| Lever type | Metal Lever t1.2 | | | | | | | | | | | |
| | C2 | | F2 | | D1 | | B1 | | E1 | | B2 | |
| Dimensions | | | | | | | | | | | | |
| Length(L) | F | 10 | 7 | 10 | 10 | 10 | 10 | 15 | 20 | 10 | | |
| | L | 15 | 10 | 15 | 15 | 20 | | | | | | |

Design and specifications presented here are for the standard parts only. Please kindly contact us for your special requests and ask for the current technical specifications before purchase and/or use.

[Back to top](#)